Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Creatronic Sp. z o.o. Sp. k.

Supplier's address: Creatronic Sp. z o.o. Sp. k., Grunwaldzka 2A, 48-340 Głuchołazy Głuchołazy

opolskie, PL

Model identifier: FX2835-120W08-3K-2SO3X1-01

_	•			
Type	Λt	light	COLL	rco.
IVDE	VI.	HEILL	3UU	ıce.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	-		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Troduct parameters							
Parameter	Value	Parameter	Value				
General product parameters:							
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	13	Energy efficiency class	F				
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 350 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000				
On-mode power (P _{on}), expressed in W	12,5	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00				
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80				

Outer	Height	1 200	Spectral power	See image	
dimensions	Width	8	distribution in the	in last page	
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	2	range 250 nm to 800 nm, at full-load		
Claim of equival	ent power ^(a)	-	If yes, equivalent power (W)	-	
			Chromaticity	0,436	
			coordinates (x and y)	0,402	
Parameters for LED and OLED light sources:					
R9 colour rendering index value		1	Survival factor	1,00	
the lumen maintenance factor		0,96			

(a)'-': not applicable;

(b)_{'-'} : not applicable;

